

Ozone Therapy

Insufflation Kit - R15 335.00



Mini Ozone Generator

Destructor; Ozone concentration: 10 - 104mg/L; oxygen input: 1/32 - 1 lpm; available for rectal and vaginal therapy and making of ozone drinking water etc; Built-in: 3 levels ozone module; built-in ozone destructor, LED indicators, cooling fan, Connector: luer lock; Input voltage: 100-240 V AC 50/60 Hz to 12 V DC



Oxygen Tank - 3 litre

3 litre oxygen tank with medical tap
Suitable for use with oxygen tank regulator



Oxygen Tank Regulator


(For use on MEDICAL oxygen tanks)

Regulate the flow of oxygen from the tank into the ozone generator; 1/32 l/m - 4 l/m; Maximum pressure - 3,000 PSI; Barb Outlet



Silicon Tube (2 metres)

Wall thickness: 1.5mm 7x4; Color: transparent;
Material: silicon; ozone-resistant



Ozone Bag for Insufflation

With 3 chambers: 200ml, 400ml, 750ml with luer connector



Luer Lock Catheters (x 2)

Fr 12 size; with 2 eyes at the tip with luer connector
single package for medical use



Male Luer Connectors (x 3)

5/32" fit for silicon hose with 4mm inner diameter



3-way Connector

Two ends with 5/32" male luer, one end with 5/32 female luer



Syringes (x 2)

60 mL/CC; luer lock

Price is subject to exchange rate fluctuations

Warranty and Disclaimer:

All products have a one year warranty from date of purchase in which repairs or exchange of parts according to that which is deemed necessary by the company will be made free of charge. This warranty does not cover damage by the following:

- 1 Misuse, abuse or alteration to the product
- 2 Damage caused by accident or neglect
- 3 Servicing or repairs made by unauthorised persons

Neither Greiner Trading CC nor its Member, shall be held responsible for any incidental, special or consequential damages resulting from the use of any products. Treatment using ozone devices are not intended as a diagnosis, cure or as a substitute for professional medical advice.

